

1	2	3	4	5	6	7	8	9	10
							ISSUE	MOD No.	INITIAL/DATE
							1		INTRODUCTION DAH 19-06-2020

60

STExCP8-PT-S CALL POINT

Maximum Power: 3.122W
Input Voltage: 48Vdc max / 250Vac 50/60Hz max

II 2G Ex db IIC T6 Gb Ta. -55°C to +70°C

CE 2813 Year / Serial No. DEMKO 15 ATEX 1589X
15/CP8PTSXXXXXX IECEx ULD 15.0018X

WARNINGS
USE COVER BOLTS CLASS A4-70
DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
POTENTIAL ELECTROSTATIC HAZARD - SEE INSTRUCTIONS
ALL ENTRIES M20x1.5 - IF TEMPERATURE EXCEEDS 70°C AT ENTRY OR 80°C AT BRANCHING POINT USE SUITABLY RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS

European Safety Systems Ltd. Impress, House, Mansell Road, London W3 7QH UK

STExCP8-PT-S

30

STExCP8-PT-D CALL POINT

Maximum Power: 6.244W
Input Voltage: 48Vdc max / 250Vac 50/60Hz max

II 2G Ex db IIC T5 Gb Ta. -55°C to +70°C
Ex db IIC T6 Gb Ta. -55°C to +60°C

CE 2813 Year / Serial No. DEMKO 15 ATEX 1589X
15/CP8PTDXXXXXX IECEx ULD 15.0018X

WARNINGS
USE COVER BOLTS CLASS A4-70
DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
POTENTIAL ELECTROSTATIC HAZARD - SEE INSTRUCTIONS
ALL ENTRIES M20x1.5 - IF TEMPERATURE EXCEEDS 70°C AT ENTRY OR 80°C AT BRANCHING POINT USE SUITABLY RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS

European Safety Systems Ltd. Impress, House, Mansell Road, London W3 7QH UK

STExCP8-PT-D

STExCP8-PB-S CALL POINT

Maximum Power: 3.122W
Input Voltage: 48Vdc max / 250Vac 50/60Hz max

II 2G Ex db IIC T6 Gb Ta. -55°C to +70°C

CE 2813 Year / Serial No. DEMKO 15 ATEX 1589X
15/CP8PBSXXXXXX IECEx ULD 15.0018X

WARNINGS
USE COVER BOLTS CLASS A4-70
DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
POTENTIAL ELECTROSTATIC HAZARD - SEE INSTRUCTIONS
ALL ENTRIES M20x1.5 - IF TEMPERATURE EXCEEDS 70°C AT ENTRY OR 80°C AT BRANCHING POINT USE SUITABLY RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS

European Safety Systems Ltd. Impress, House, Mansell Road, London W3 7QH UK

STExCP8-PB-S

STExCP8-PB-D CALL POINT

Maximum Power: 6.244W
Input Voltage: 48Vdc max / 250Vac 50/60Hz max

II 2G Ex db IIC T5 Gb Ta. -55°C to +70°C
Ex db IIC T6 Gb Ta. -55°C to +60°C

CE 2813 Year / Serial No. DEMKO 15 ATEX 1589X
15/CP8PBDXXXXXX IECEx ULD 15.0018X

WARNINGS
USE COVER BOLTS CLASS A4-70
DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
POTENTIAL ELECTROSTATIC HAZARD - SEE INSTRUCTIONS
ALL ENTRIES M20x1.5 - IF TEMPERATURE EXCEEDS 70°C AT ENTRY OR 80°C AT BRANCHING POINT USE SUITABLY RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS

European Safety Systems Ltd. Impress, House, Mansell Road, London W3 7QH UK

STExCP8-PB-D

STExCP8-PM-S CALL POINT

Maximum Power: 3.122W
Input Voltage: 48Vdc max / 250Vac 50/60Hz max

II 2G Ex db IIC T6 Gb Ta. -55°C to +70°C

CE 2813 Year / Serial No. DEMKO 15 ATEX 1589X
15/CP8PMSXXXXXX IECEx ULD 15.0018X

WARNINGS
USE COVER BOLTS CLASS A4-70
DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
POTENTIAL ELECTROSTATIC HAZARD - SEE INSTRUCTIONS
ALL ENTRIES M20x1.5 - IF TEMPERATURE EXCEEDS 70°C AT ENTRY OR 80°C AT BRANCHING POINT USE SUITABLY RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS

European Safety Systems Ltd. Impress, House, Mansell Road, London W3 7QH UK

STExCP8-PM-S

STExCP8-PM-D CALL POINT

Maximum Power: 6.244W
Input Voltage: 48Vdc max / 250Vac 50/60Hz max

II 2G Ex db IIC T5 Gb Ta. -55°C to +70°C
Ex db IIC T6 Gb Ta. -55°C to +60°C

CE 2813 Year / Serial No. DEMKO 15 ATEX 1589X
15/CP8PMDXXXXXX IECEx ULD 15.0018X

WARNINGS
USE COVER BOLTS CLASS A4-70
DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
POTENTIAL ELECTROSTATIC HAZARD - SEE INSTRUCTIONS
ALL ENTRIES M20x1.5 - IF TEMPERATURE EXCEEDS 70°C AT ENTRY OR 80°C AT BRANCHING POINT USE SUITABLY RATED CABLE AND CABLE GLANDS - SEE INSTRUCTIONS

European Safety Systems Ltd. Impress, House, Mansell Road, London W3 7QH UK

STExCP8-PM-D

DRAWING TO BS8888:2000 GEOMETRIC TOLERANCES TO ISO1101:1983 LINEAR DIMENSIONAL TOLS +/-0.35mm ANGULAR DIMENSIONAL TOLS +/-2 deg	DRAWN D HOWGILL DATE 19-06-20 CHECKED R N POTTS DATE 19-06-20 APPROVED R N POTTS DATE 19-06-20	SURFACE FINISH MATERIAL ALTERNATIVE MATERIAL	WEIGHT (Kg)	THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER THEREIN IS COMMUNICATED IN CONFIDENCE AND IS THE COPYRIGHT PROPERTY OF EUROPEAN SAFETY SYSTEMS LTD. NEITHER THE WHOLE OR ANY EXTRACT MAY BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING OR TENDERING PURPOSES WITHOUT THEIR WRITTEN CONSENT. © EUROPEAN SAFETY SYSTEMS LTD. AS PER LATEST DATE OF ISSUE SHOWN ABOVE	 EUROPEAN SAFETY SYSTEMS LTD IMPRESS HOUSE MANSELL ROAD ACTON LONDON W3 7QH WWW.E2S.COM	ALL DIMENSIONS IN MM IF IN DOUBT, ASK - DO NOT SCALE TITLE STEx CP8 PT / PB / PM PUSH BUTTON CALL POINT PRODUCT LABEL SCALE 1:1 SHEET 1 of 1 DRAWING NUMBER D204-09-201	
--	--	--	-------------	---	---	--	--