EU-TYPE EXAMINATION CERTIFICATE



Equipment or Protective System intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU

- EU-Type Examination Certificate Number: DEMKO 19 ATEX 2101X Rev. 1 [3]
- Product: GNExCP7 Call Point Switch [4]

[1]

[2]

- Manufacturer: European Safety Systems Ltd. [5]
- Address: Impress House, Mansell Road, Acton, London W3 7QH United Kingdom [6]
- [7] This product and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred
- UL International Demko A/S, notified body number 0539 in accordance with Article 17 of the Council Directive 2014/34/EU of 26 [8] February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential report no. DK/ULD/ExTR19.0007/01.

[9] Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN IEC 60079-0:2018

EN 60079-1:2014

EN 60079-31:2014

- [10] If the sign "X" is placed after the certificate number, it indicates that the product is subject to special conditions for safe use specified in the schedule to this certificate.
- [11] This EU-Type Examination Certificate relates only to the design and construction of the specified product. Further requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by the certificate.
- [12] The marking of the product shall include the following:



── II 2 D Ex tb IIIC T90°C...T80°C Db

Certification Manager

Jan-Erik Storgaard


This is to certify that the sample(s) of the Product described herein ("Certified Product") has been investigated and found in compliance with the Standard(s) indicated on this Certificate, in accordance with the ATEX Product Certification Program Requirements. This certificate and test results obtained apply only to the product sample(s) submitted by the Manufacturer. UL did not select the sample(s) or determine whether the sample(s) provided were representative of other manufactured product. UL has not established Follow-Up Service or other surveillance of the product. The Manufacturer is solely and fully responsible for conformity of all product to all applicable Standards, specifications, requirements or Directives. The test results may not be used, in whole or in part, in any other document without UL's prior written approval.

Date of issue: 2019-04-30 Re-issued: 2021-10-22

Notified Body

UL International Demko A/S, Borupvang 5A, 2750 Ballerup, Denmark Tel. +45 44 85 65 65, info.dk@ul.com, www.ul.com

Page 1 of 3



[13]

EU-TYPE EXAMINATION CERTIFICATE No. DEMKO 19 ATEX 2101X Rev. 1

Schedule

[15] <u>Description of Product</u>

[14]

The GNEx CP7 series Call Points are made from GRP material and provide Ex db and Ex tb types of protection. There are four variants, Break Glass, Push Button, Momentary Push Button and Push Button & Tool Reset. All models have a flanged flamepath for the cover and a cylindrical flamepath for the operating rods. All variants have three M20 x 1.5p threaded entries, two are located at the top of the base and one is located on the side of the base. The permitted orientations for the equipment are vertical only with the double cable entry uppermost or lowermost only.

Each variant may incorporate single or dual microswitch configurations, DIN rail mounted terminal blocks and PCB terminal. End of line and series monitoring resistors or diodes may be fitted when supplied at 24 or 48 Vdc.

GNEX CP7- PB- S

I – Enclosure Series

GNEx - Primary Enclosure Series

II – Certifications

CP7- - Call Point 7

III - Type of Enclosure

BG- - Break Glass

PB- - Push Button

PM- - Momentary Push Button

PT- - Push Button & Tool Reset

IV - Switch configuration Width of Enclosure

S - Single microswitch

D - Dual microswitch

Temperature range

The relation between ambient temperature and the assigned temperature class is as follows:

Model	Maximum Ambient (-55°C to xx°C)			
	Gas		Dust	
	+60°C	+65°C	+70°C	+70°C
GNExCP7-PB-S	T6	-	T5	T90°C
GNExCP7-PB-D	T6	-	T5	T90°C
GNExCP7-PM-S	T6	-	T5	T90°C
GNExCP7-PM-D	T6	-	T5	T90°C
GNExCP7-PT-S	T6	-	T5	T90°C
GNExCP7-PT-D	T6	-	T5	T90°C
GNExCP7-BG-S	-	-	T6	T80°C
GNExCP7-BG-D	-	T6	T5	T85°C

Electrical data

Note: The DC models are limited to maximum 6.224W controlled by the allowable component configuration.

The AC models are limited to 5W by design.

250Vac max / 5.0A max (for units without any series resistor or end of line devices only)

48Vdc max / 1.0A max

24Vdc max / 3.0A max

Routine tests

Routine tests according to EN 60079-1 cl. 16 are not required, as the enclosures have been successfully tested at four times the reference pressure.

[16] <u>Descriptive Documents</u>

The scheduled drawings are listed in the report no. provided under item no. [8] on page 1 of this EU-Type Examination Certificate.

[17] Specific conditions of use:

- No repair to the flameproof joints is permitted
- The equipment has a maximum capacitance of 6.33pF
- Equipment is permitted to be wall mounted only in the vertical position. The enclosure base is permitted in two mounting positions, with the double cable entry lowermost or uppermost.

[18] <u>Essential Health and Safety Requirements</u>

The Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9.



[13]

[14]

Schedule EU-TYPE EXAMINATION CERTIFICATE No. DEMKO 19 ATEX 2101X Rev. 1

Additional information



the trademark warning signals will be used as the company identifier on the marking label.

The manufacturer shall inform the notified body concerning all modifications to the technical documentation as described in Annex III to Directive 2014/34/EU of the European Parliament and the Council of 26 February 2014.

